ULTRA-LOK™ LEADING EDGE

SAFER. VERSATILE.

A FOOT-LEVEL TIE-OFF AND LEADING EDGE UNIT THAT FITS THE JOB.

Right-size gear works smarter, like you. That's why we've expanded the Ultra-Lok™ leading edge product line to include a 15-foot (4.6 m) retractable. The Ultra-Lok Leading Edge line of retractables includes lengths from 15' (4.6 m) to 55' (16.8 m), are compliant for leading edge work and foot-level tie-off, providing superior protection against sharp, leading edges.

Shown with optional concrete tripod **#2105500***

*Fits 15' and 30' models only

DBI SALA®

ULTRA-LOK™ LEADING EDGE

Model above shown with optional counterweight anchor **#7255000**

DO YOU EVER DO WORK NEAR A LEADING EDGE?

The Ultra-Lok™ Leading Edge SRL allows the user to tie-off at their feet while providing protection against the sharp, abrasive leading edges found at many construction sites.

FEATURES AND BENEFITS

- **Lightweight and Durable:** Smaller and lighter, the new 15' (4.6m) unit leverages industry-leading Ultra-Lok technology.
- **Arresting Capabilities:** The external shock absorber and speed-sensing brake limit forces for the highest level of safety.
- **Versatility:** With multiple lengths and both permanent and temporary anchor methods available, it's easy to configure the ultimate fall protection system.

Shown with optional roof anchor **#2105683***

SPECIFICATIONS

- Wire Rope: 7/32 in. (5.5 mm) galvanized minimum tensile strength 5,600 lb. (25kN)
- Housing: Thermoplastic
- Snap Hook: Alloy steel, zinc plated, 5,000 lb. (22 kN) minimum tensile strength, 3,600 lb. (16 kN) gate
- Energy Absorber: Fully integrated into lifeline
- Capacity: 310 lb. (140 kg)
- Maximum Arresting Force: 900 lb. (4 kN)
- Standards: OSHA 1926.502, OSHA 1910.66, ANSI Z359.14 and CSA Z259.2.2

Specifications:

USA Part #	CA Part#	Length	Weight	Size
3504422	3504422C	15' (4.6 m)	11lb. (5.0 kg)	10.5" (27 cm) x 7" (18 cm) x 3" (8 cm)
3504500	3504500C	30' (9.1 m)	16lb. (7.3 kg)	11.5" (29 cm) x 7" (18 cm) x 3" (8 cm)
3504600	3504600C	55' (16.8 m)	30lb. (13.6 kg)	12" (31 cm) x 10" (25 cm) x 4.5" (11 cm)

*Fits 15' and 30' models only

capital SAFETY

Capital Safety - USA: 800 328 6146
Canada: 800 387 7484 Latin America: +1 651 385 4301
Asia: +65 65587758 Germany: +49 (0)30 92 03 83 87 00
New Zealand: 0800 212 505 Australia: 1800 245 002
Europe, Middle East, Africa: +33 (0)4 97 10 00 10
Northern Europe: +44 (0)1527 548000
www.capitalsafety.com **info@capitalsafety.com**

© 2014 Capital Safety

Form: 9700849 Rev. C