

Miller 8183 Cross-Arm Anchorage Strap

Description

The 8183 Cross-Arm Strap wraps around I-beams and other structures and attaches with a 2-inch (50mm) D-ring that slips through a 3-inch (76mm) D-ring to form a secure attachment point for lanyards and other connecting devices.

Materials

Webbing: 2" (50mm) Polyester webbing
D-Rings: Steel; 2" (50mm) and 3" (76mm) diameter
Thread: Six-cord bonded, three-strand polyester thread.
Labels: Valeron

*All hardware meets ASTM (50) fifty-hour salt spray test requirements

Technical

Maximum Working

Load Capacity: 400 lbs (181.4 kg)
Webbing: 5,000 lbs (22 kN) minimum tensile strength
D-Rings: 5,000 lbs (22 kN) minimum tensile strength
Thread: 42 lbs (19 kg) minimum tensile strength
***Length:** 6 ft (1.8m) standard length
 *Additional lengths available



Certification

OSHA 1926.502, OSHA 1910.66, ANSI A10.32 and ANSI Z359-2007

MILLER®

by Honeywell

Toll Free 800.873.5242 (press 4) • hsptechsupport@honeywell.com • www.millerfallprotection.com

⚠ WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.