NEW!

Miller Fusion™ Roof Anchor Post Permanent or Temporary Solution for Roof Safety



- Adapts to a wide range of roof designs
- Quick and easy install, reducing installation time by more than 50%
- Attaches to the surface of existing roof structures, eliminating the need for roof penetration and repair
- Protects the structure during a fall with a unique energy-absorbing load distribution system



Miller Fusion[™] Roof Anchore Post

The new versatile, single-point **Miller Fusion Roof Anchor Post** adapts to a wide range of roof designs with its innovative base plate engineered for temporary or permanent installation to the roof surface.

When properly installed, a dependable fall protection connection is established. Should a fall occur, forces are reduced with its energy-absorbing design to maintain a secure connection to the structure.

The easy-to-install **Miller Fusion Roof Anchor Post** is designed for quick set-up and does not require roof penetration to sub-surface rafters or trusses.

a finitizione



Modular bar extenders accommodate additional standing seam widths.

- Versatile single-point anchor adapts to a variety of roof designs – With a variety of models available, the Miller Fusion Roof Anchor Post can accommodate most industrial roof designs including standing seam, membrane, built-up, metal sheathing, concrete and wood.
- Attaches to the surface of existing roof structures Quick, easy installation reduces cost requiring minimal labor and eliminating the need for roof penetration and repair.
- Significantly reduces the fall forces on the roof structure – In the event of a fall, the top of the Miller Fusion Roof Anchor Post reorients with the force in a direct line and activates the patent-pending energy absorber.
- Durable design that withstands the changing outdoor environment – Internal components are constructed of stainless steel. The steel post and base are plated with zinc followed by a premium powder coating for two layers of protection.
- Models for steel decking, concrete and wood can be used on other non-roof structures.





In the event of a fall, the Miller Fusion Roof Anchor Post orients in the direction of the force, the built-in, energy-absorbing component activates and the base remains securely attached to the roof surface.

Miller Fusion Roof Anchor Post adapts to a variety of roof structures



SKU X10001



SKU X10011



SKU X10030/X10031

Standing Seam Design

- Aluminum clamping mechanism is designed to pre-install to the base plate and is self centering for easy installation.
- The clamping bolts are tightened from above the plate for easy fastening and inspection.
- Can be used for permanent and temporary installations.
- Three models are available to accommodate standing seam spacing up to 24-inches (610 mm).*

Metal Sheathing Design

- Designed to attach to metal sheathing with a minimum 24 gauge (0.024-inch [.61 mm]) thickness.
- Hardware kit includes sealing materials to prevent water damage to roof.

Membrane/Built-up Design

- Easy-to-install toggle kit fastens through membrane, insulation and into metal sheathing, wood sheathing or concrete.
- Models available for built-up roof thicknesses accommodate up to 10.5 inches (267 mm).



SKU X10040





SKU X10020

Applications

- Roof inspection and maintenance
- Air conditioning, ventilation fan and solar panel maintenance
- Skylight cleaning
- Debris removal from gutters
- Installation and maintenance of satellite dishes and other communication systems

Wood Design

- Includes lag screw kit.
- Installs into plywood with minimum thickness of 5/8-inch (15.9 mm) CDX.
- Designed for temporary installation only.

Concrete Decking Design

- Includes concrete expansion anchor kit.
- Installs into concrete decking with minimum thickness of 6.5 inches (165 mm) and minimum concrete compressive strength of 3000 PSI (20.7 MPa).

Multi-Purpose Metal Sheathing, Wood and **Concrete Design**

- This multi-purpose post uses the same base as models X10011. X10040 and X10050.
- Miller specified hardware must be purchased for this base. (This model does not include hardware.)

*Complete list of models (SKUs) on back page.







	A	D	L L	U
X10000 X10010		18.0 in. (457 mm)		
X10001 X10011 X10020 X10040 X10050	15.25 in. <i>(387 mm)</i>	22.0 in. (559 mm)	8.6 in. (218 mm)	4.0 in. (102 mm)
X10030 X10031			9.0 in. <i>(229 mm)</i>	
X10002	15.6 in. <i>(396 mm)</i>	26.0 in. (660 mm)	9.56 in. <i>(243 mm)</i>	

Specifications

Roof Anchor Post Materials

Energy Absorber:	Stainless Steel
Internal Connecting Components:	Stainless Steel
Top and Bottom Post Plates:	Anodized Cast Aluminum
Standing Seam/Wood/Metal Base Plate:	Two-layer Zinc/Powder-Coated Steel
Post Tube:	Zinc/Powder-Coated Steel
Post/Base Plate Seal:	HDPE
Post Cap:	Vinyl w/UV Inhibitor

Connection Components Materials

Standing Seam Clamps:	Anodized Aluminum/Stainless Steel	
Extender Bar for Standing Seams:	Anodized Aluminum/Stainless Steel	
Hardware for Metal Sheathing:	Hot Dip Galvanized/Neoprene	
Hardware for Membrane:	Zinc-Plated Steel/PVC/Neoprene	
Hardware for Wood:	Zinc-Plated Steel	
Hardware for Concrete:	Stainless Steel	
Performance		
Activation Force:	1000 lbs. (4.4 kN)	
Maximum Capacity:	310 lbs. (140.6 kg)	

Fusion Roof Anchor Post

SKU	Description	Designed to Accomodate
STAND	DING SEAM ROOFING - Includes post with base and st	anding seam clamping assembly kit
X10000	Small base	Standing seam spacing from 11.75 in. (298 mm) to 17 in. (432 mm)
X10001	Large base	Standing seam spacing from 11.75 in. (298 mm) to 21.25 in. (540 mm)
X10002	Large base & extension bars	Standing seam spacing from 11.75 in. (298 mm) to 24 in. (610 mm)
METAL	. SHEATHING ROOFING – Includes post with base and	I rivet kit with sealing washers and mastic tape
X10010	Small base	Metal sheathing w/minimum thickness of 24 gauge (0.024 in. [0.61 mm])
X10011	Large base	Metal sheathing w/minimum thickness of 24 gauge (0.024 in. [0.61 mm]). Trapezoidal spacing of 8 in. (203 mm) to 20 in. (508 mm) in one-inch (25.4 mm) increments.
MEMBI	RANE/BUILT-UP ROOFING - Includes post with base	and toggle bolt kit
X10030	Up to 5.5 in. (140 mm) thickness	Fastens through membrane, insulation & into metal sheathing, wood sheathing or concrete with a combined thickness of up to 5.5 in. <i>(140 mm)</i>
X10031	> 5.5 in. (140 mm) & up to 10.5 in. (267 mm) thickness	Fastens through membrane, insulation & into metal sheathing, wood sheathing or concrete with a combined thickness of > 5.5 in. (140 mm) up to 10.5 in. (267 mm)
WOOD	SHEATHING (TEMPORARY INSTALLATIONS O	NLY) – Includes post with base and lag screw kit
X10040	Wood sheathing	Plywood with minimum thickness of 5/8-in. (15.9 mm) CDX
CONC	RETE ROOFING – Includes post with base and concrete e	expansion bolt anchor kit
X10050	Concrete	Concrete decking with minimum thickness of 6.5 in. (165 mm) & minimum concrete compressive strength of 3000 PSI (20.7 MPa)
MULTI-	PURPOSE METAL SHEATHING, WOOD AND CO	DINCRETE ROOFING (NO HARDWARE INCLUDED) ation. See instruction manual for hardware specifications.
X10020	Metal sheathing, wood or concrete	 Metal sheathing w/minimum thickness of 24 gauge (0.024 in. [0.61 mm]) Trapezoidal spacing of 8 in. (203 mm) to 20 in. (508 mm) in one-inch (25.4 mm) increments. Plywood with minimum thickness of 5/8-in. (15.9 mm) CDX Concrete decking with minimum thickness of 6.5 in. (165 mm) & minimum concrete compressive strength of 3000 PSI (20.7 MPa)

Meets or exceeds all applicable industry standards including OSHA, ANSI A10.32 and Z359.1-2007.

A This equipment should only be used after reading the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.



by Honeywell

Ask the Expert ... Ask Miller.

800/873-5242 www.millerfallprotection.com

LMFRP

