

Titan™ Pack-Type Shock-Absorbing Lanyard

Model: T6111/

Description

The T6111 with Pack-Type shock-absorber is designed to reduce fall arrest forces.

The integral Pack-Type shock-absorber has a specially-woven inner core that smoothly deploys during a fall arrest.

Materials

Webbing

Lanyard:

1in. polyester

Shock-absorbing

web core:

polyester

Safety strap:

1-1 ¾ in. polyester

Thread:

6 cord bonded 3 strand polyester thread with a min. tensile of 42 lbs.

Hardware:

Steel

Locking Snap Hooks:

5,000 lb (22kN), ¾ in. (19mm) gate opening.

Label:

Valeron

* All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Technical

Max. Working Load: 310 lbs (141kg)

Min. Tensile (webbing): 5,000 lbs (0.31kg)

Min. Tensile (snaps): 5,000 lbs (0.31kg)

Certification

Meets applicable OSHA 1926.502 , ANSI A10.32 and CSA Z259.11 requirements.

T6111/6FTAK



Additional lengths available.



by Honeywell

Toll Free 800.873.5242 (press 4) • hsp techsupport@honeywell.com • www.millerfallprotection.com

⚠ WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION **PRODUCTS** AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.