

## SPECIAL FEATURES:

9.75 base curved lens provides full side protection without distracting seams or traditional type side shields.

Nose buds secure the glass and prevent slipping while providing a pillow soft fit.

Lenses are coated for superior scratch resistance.

Lenses provide 99% protection against harmful UV rays.

Venture II® Ballistic passes MIL-PRF-31013 Ballistic Standards and meets the ANSI Z87.1-2003 High Velocity Impact Standard.

## **GENERAL SPECIFICATIONS**

PD Lens Thickness: 2.2mm 68mm Lens Base 9.75 curve Weight 27gm Lens size vertical 45mm Lens Size Diagonal 56mm Temple length (lens-tip) Bridge 10.5mm 150-163mm

Overall Width (hinge-hinge) 142mm

## FRAME AND LENS OPTIONS:

Frame colors: Black, Metallic blue, Metallic maroon and Slate grey
Lens options: Clear, Grey, Amber, Silver Mirror, Blue Mirror, Gold Mirror,

Indoor/Outdoor Mirror

COMPONENT	MATERIAL	FEATURES	
Lens	Polycarbonate	high curve dual lens, side shield integrated to lens	
Frame	Polycarbonate	lens removeable from frame	
	Nylon 6.6	matte finish	
Side Shield	Polycarbonate	integral to lens	
Nose piece	V bridge-PC	V bridge holds pad in place	
	Soft pad-TPR	TPR = thermoplastic elastormer	
Sleeve (on temple)	Nylon 6.6	adjustable to 4 length positions	
Temple	Nylon 6.6	adjustable	
Temple tip	n/a	n/a	
Hinge	PC/nylon	3 barrel type, integral to frame/sleeve	
Screw	Stainless Steel sta	Stainless Steel standard hinge screw	

**MARKINGS** 

**PACKAGING** 

**STANDARDS** 

MEETS ANSI Z87.1 STANDARDS

TEST RESULTS AVAILABLE UPON REQUEST